

## Fujitsu Deskbound Devices PCs

The Fujitsu ESPRIMO family is a complete range of highly expandable PCs that run your office applications dependably. Outstanding production quality ensures reliability, and patented 0-Watt technology reduces energy costs by 70% compared with legacy PCs. Individual configurations and the unique DeskView Load preinstallation solution ensure you can minimize rollout and management costs for years to come.



Value

### All-round

Standard Applications  
e.g. internet,  
e-mailing,  
office application

ESPRIMO P5xx  
ESPRIMO E5xx  
ESPRIMO P4xx  
ESPRIMO E4xx

### Advanced

Complex Applications  
e.g. spreadsheets,  
documents,  
presentations,  
databases, video,  
standard manageability

ESPRIMO P7xx  
ESPRIMO E7xx  
ESPRIMO C7xx

### Superior

High performance  
manageable  
computing,  
flexible integration  
into infrastructures

ESPRIMO P9xx  
ESPRIMO E9xx  
ESPRIMO Q9xx

Functionality

Superior PCs  
ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO E900 E85+
Operating system*	Your Desktop PC Without Any Compromises Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3062 (ATX)
Chipset	Intel® Q67
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	6
thereof eSATA	2 (optional)
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI, Raid 1/0
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 LM
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix
Country-specific Standard Warranty and Service Level**	3 years Bring-In / On-Site Service

# Superior PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO E900 E90+
	Your Desktop PC Without Any Compromises
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3062 (ATX)
Chipset	Intel® Q67
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	6
thereof eSATA	2 (optional)
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI, Raid 1/0
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB

Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 LM
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 88% / 92% / 91%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 92% energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, Switched monitor outlet
Country-specific Standard Warranty and Service Level **	3 years Bring-In / On-Site Service

# Superior PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO E900 0-Watt
	The Innovative 0-Watt PC
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3062 (ATX)
Chipset	Intel® Q67
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	6
thereof eSATA	2 (optional)
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI, Raid 1/0
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB

Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 LM
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 91% / 94% / 92%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 94% energy efficient power supply, 0-Watt in off-mode, Zero Noise PC, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, Switched monitor outlet
Country-specific Standard Warranty and Service Level **	3 years Bring-In / On-Site Service



Fujitsu	ESPRIMO P900 E85+		
	The Expandable Business Workhorse	Audio codec	Conexant CX20642
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit	LAN	10/100/1000 Mbit/s Intel® 82579 LM
Facts mainboard	D3062 (ATX)	Dimensions (W x D x H)	175 x 419 x 395 mm
Chipset	Intel® Q67	Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz	Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules	Country-specific Standard Warranty and Service Level **	3 years Bring-In / On-Site Service
Serial ATA	6		
thereof eSATA	2 (optional)		
thereof SATA III	2		
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI, Raid 1/0		
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I		
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch		
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay		
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots		
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)		
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB		



Fujitsu	ESPRIMO P900 E90+
	The Expandable Business Workhorse
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3062 (ATX)
Chipset	Intel® Q67
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	6
thereof eSATA	2 (optional)
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI, Raid 1/0
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB

Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 LM
Dimensions (W x D x H)	175 x 419 x 395 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 88% / 92% / 91%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 92% energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, Switched monitor outlet
Country-specific Standard Warranty and Service Level **	3 years Bring-In / On-Site Service



Fujitsu	ESPRIMO P900 0-Watt
	The Innovative 0-Watt PC
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3062 (ATX)
Chipset	Intel® Q67
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	6
thereof eSATA	2 (optional)
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI, Raid 1/0
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB

Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 LM
Dimensions (W x D x H)	175 x 419 x 395 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 91% / 94% / 92%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 94% energy efficient power supply, 0-Watt in off-mode, Zero Noise PC, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, Switched monitor outlet
Country-specific Standard Warranty and Service Level **	3 years Bring-In / On-Site Service

# Superior PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO Q900
	The Mini with More PC per cm²
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Chipset	Intel® QM67
Processor type, Second level cache, Processor frequency	Intel® Core™ i5-2520M processor, 3 MB, 2.5 GHz Intel® Core™ i3-2330M processor, 3 MB, 2.2 GHz Intel® Pentium® processor B940, 2 MB, 2.0 GHz Intel® Celeron® processor B800, 2 MB, 1.5 GHz
Serial ATA	1
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
Drives (optional)	Card Reader 8-in-1 ESPRIMO Q Blu-ray Combo SATA Slot-in slim, SATA DVD Super Multi Slot-in slim, SATA
Hard disk drive	SATA, 5400 rpm, 250 GB, 2.5-inch HDD SATA II, 5400 rpm, 320 GB, 2.5-inch HDD SATA II, 5400 rpm, 500 GB, 2.5-inch HDD SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SSD SATA, 128 GB, 2.5-inch, full disk encryption
Drive bays	1 x 2.5-inch bay 1 x 5.25-inch external bay
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 (optional) x Audio: line-out / headphones / SPDIF 2 x USB 3.0 total 5 x USB 2.0 total 2 x USB front 5 x USB rear 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Ethernet (RJ-45) 1 x Kensington Lock support 1 (DVI-I) x DVI 1 x DisplayPort
Graphics	Intel® HD Graphics or HD Graphics 3000 (depending on CPU), up to 1759 MB
Audio codec	Realtek ALC662
LAN	10/100/1000 Mbit/s Intel® 82579 LM 1 (optional) x Integrated WLAN
Dimensions (W x D x H)	165 x 168 x 57 mm
Power efficiency	Power supply efficiency (at 230 V; 20 % / 50 % / 100 % load): 87 % / 90 % / 87 %
Special features	ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), Mobile on Desktop, Backpack Solution, Extremely space-saving design, Intel® vPro™ technology and DeskView Manageability, Embedded Security (TPM), external power supply
Country-specific Standard Warranty and Service Level**	3 years Bring-In / On-Site Service



# Advanced PCs

## ESPRIMO



Fujitsu	ESPRIMO E705 E85+
	Your Desktop PC Without Any Compromises
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3091 (ATX)
Chipset	AMD 880G
Processor type, Second level cache, Processor frequency	AMD Athlon™ FX 4100, 8 MB, 3.6 GHz AMD Phenom™ II X4 960T, 8 MB, 3.0 GHz AMD Phenom™ II X2 560, 7 MB, 3.3 GHz AMD Athlon™ II X2 265, 2 MB, 3.3 GHz AMD Athlon™ II X2 220, 1 MB, 2.8 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	6
thereof eSATA	1 (optional)
Controller functions	Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay; 1 x 3.5-inch internal bay; 1 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; optional USB 3.0 total; 12 x USB 2.0 total; 4 x USB front; 6 x USB rear; 2 x USB internal; 1 (via DVI to VGA adapter, part of shipment) x VGA; 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible); 1 (optional) x Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 (Dual link DVI-I) x DVI; 1 (optional) x eSATA; 1 x DisplayPort; 2 x Mouse / Keyboard (PS/2)
Graphics	ATI Radeon® HD 4250, up to 2811 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Broadcom BCM57780
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
Special features	ENERGY STAR®, Green PC, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply, Family Concept, Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, DASH optional, halogen free mainboard
Country-specific Standard Warranty and Service Level**	1 year Bring-In / On-Site Service

Fujitsu recommends Windows® 7.



ESPRIMO P705 E85+
The Expandable Business Workhorse
Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
D3091 (ATX)
AMD 880G
AMD Athlon™ FX 4100, 8 MB, 3.6 GHz AMD Phenom™ II X4 960T, 8 MB, 3.0 GHz AMD Phenom™ II X2 560, 7 MB, 3.3 GHz AMD Athlon™ II X2 265, 2 MB, 3.3 GHz AMD Athlon™ II X2 220, 1 MB, 2.8 GHz
Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
6
1 (optional)
Serial ATA II, NCQ and 3 Gbit, AHCI, Raid 1/0
MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
2 x 3.5-inch external bay; 2 x 3.5-inch internal bay; 2 x 5.25-inch external bay
1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; optional USB 3.0 total; 12 x USB 2.0 total; 4 x USB front; 6 x USB rear; 2 x USB internal; 1 (via DVI to VGA adapter, part of shipment) x VGA; 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible); 1 (optional) x Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 (Dual link DVI-I) x DVI; 1 (optional) x eSATA; 1 x DisplayPort; 2 x Mouse / Keyboard (PS/2)
ATI Radeon® HD 4250, up to 2811 MB
Realtek ALC663
10/100/1000 Mbit/s Broadcom BCM57780
175 x 419 x 395 mm
Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
ENERGY STAR®, Green PC, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply, Family Concept, Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, DASH optional, halogen free mainboard
1 year Bring-In / On-Site Service

# Advanced PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO E700 E85+
	Your Desktop PC Without Any Compromises
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3061 (ATX)
Chipset	Intel® Q65
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	5
thereof eSATA	2 (optional)
thereof SATA III	1
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch mSATA, 2 GB, Flash drive mSATA, 4 GB, Flash drive mSATA, 8 GB, Flash drive mSATA, 16 GB, Flash drive SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots

Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 V
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83 % / 86 % / 85 %
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 86 % energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix
Country-specific Standard Warranty and Service Level **	1 year Bring-In / On-Site Service

# Advanced PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO E700 E90+
	Your Desktop PC Without Any Compromises
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3061 (ATX)
Chipset	Intel® Q65
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	5
thereof eSATA	2 (optional)
thereof SATA III	1
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch mSATA, 2 GB, Flash drive mSATA, 4 GB, Flash drive mSATA, 8 GB, Flash drive mSATA, 16 GB, Flash drive SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots

Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 V
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 88% / 92% / 91%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 92 % energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, Switched monitor outlet
Country-specific Standard Warranty and Service Level **	1 year Bring-In / On-Site Service

# Advanced PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO P700 E85+		
	The Expandable Business Workhorse	Audio codec	Conexant CX20642
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit	LAN	10/100/1000 Mbit/s Intel® 82579 V
Facts mainboard	D3061 (ATX)	Dimensions (W x D x H)	175 x 419 x 395 mm
Chipset	Intel® Q65	Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz	Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules	Country-specific Standard Warranty and Service Level **	1 year Bring-In / On-Site Service
Serial ATA	5		
thereof eSATA	2 (optional)		
thereof SATA III	1		
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI		
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I		
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch		
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay		
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots		
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)		
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB		

Advanced PCs

ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO P700 E90+
	The Expandable Business Workhorse
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3061 (ATX)
Chipset	Intel® Q65
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	5
thereof eSATA	2 (optional)
thereof SATA III	1
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	2 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	1 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI-Express 2.0 x4 (mech. x16) 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 14 x USB 2.0 total 4 x USB front 8 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB

Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 V
Dimensions (W x D x H)	175 x 419 x 395 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 88% / 92% / 91%
Special features	Green PC, Halogen free mainboard, ENERGY STAR®, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 92% energy efficient power supply, True family concept, EraseDisk functionality, Embedded Security (TPM), Keyboard power on, Service-friendly cabinet with EasyChange, EasyFix, Switched monitor outlet
Country-specific Standard Warranty and Service Level **	1 year Bring-In / On-Site Service

# Advanced PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO C700
	The Ultra Small Professional PC
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D3064 (proprietary)
Chipset	Intel® Q65
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules). > 16 GB support with future memory modules
Serial ATA	3
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
Drives (optional)	DVD Super Multi, SATA I DVD Super Multi Slot-in slim, SATA
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch mSATA, 2 GB, Flash drive mSATA, 4 GB, Flash drive mSATA, 8 GB, Flash drive mSATA, 16 GB, Flash drive SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch internal bay 1 x 5.25-inch external bay 1 x 5.25-inch external bay slim
Slots	1 x PCI-Express 2.0 x16
Interfaces	1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 12 x USB 2.0 total 4 x USB front 6 x USB rear 2 x USB internal 1 (via DVI to VGA adapter, part of shipment) x VGA 2 x Serial (RS-232, powered, 9pin, 16 byte FIFO, 16550 compatible) 1 (optional) x Parallel (25pin with EPP and ECP) 1 x Ethernet (RJ-45) 1 (DVI-I) x DVI 1 (optional) x eSATA 1 x DisplayPort 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Audio codec	Conexant CX20642
LAN	10/100/1000 Mbit/s Intel® 82579 V
Dimensions (W x D x H)	265 x 315 x 88 mm

Power efficiency	Power supply efficiency (at 230 V; 20 % / 50 % / 100 % load): 87 % / 90 % / 87 %
Special features	Green PC, ENERGY STAR® 5.0, Blue Angel certified, EPEAT® Gold (dedicated regions), up to 90 % energy efficient power supply, Powered Serial Ports, Family Concept, Service-friendly cabinet with EasyChange, EasyFix
Country-specific Standard Warranty and Service Level **	1 year Bring-In / On-Site Service

# All-round PCs

## ESPRIMO



Fujitsu	ESPRIMO E500 E85+
	Your Flexible Economy PC
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D2991 (ATX)
Chipset	Intel® B65
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
Serial ATA	4
thereof eSATA	1 (optional)
thereof SATA III	1
Controller functions	Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay; 1 x 3.5-inch internal bay; 1 x 5.25-inch external bay
Slots	2 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI slots
Interfaces	1 x Audio: line-in / microphone; 1 x Audio: line-out; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; optional USB 3.0 total; 10 x USB 2.0 total; 2 x USB front; 6 x USB rear; 2 x USB internal; 1 x VGA; 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible); 1 (optional) x Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 (DVI-D) x DVI; 1 (optional) x eSATA; 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics 2000, up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Realtek RTL 8111E
Dimensions (W x D x H)	340 x 382 x 98 mm
Power efficiency	Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
Special features	ENERGY STAR® 5.0, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply, Service-friendly cabinet with EasyChange, EasyFix
Country-specific Standard Warranty and Service Level **	1 year Bring-In / On-Site Service

Fujitsu recommends Windows® 7.



ESPRIMO P500 E85+
Your Flexible and Economic PC
Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
D2991 (ATX)
Intel® B65
Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Up to 32 GB, 4 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
4
1 (optional)
1
Serial ATA II (3 Gbit), Serial ATA III (6 Gbit), NCQ, AHCI
MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
1 x 3.5-inch external bay; 2 x 3.5-inch internal bay; 2 x 5.25-inch external bay
2 x PCI-Express x1 1 x PCI-Express 2.0 x16 1 x PCI slots
1 x Audio: line-in / microphone; 1 x Audio: line-out; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; optional USB 3.0 total; 10 x USB 2.0 total; 2 x USB front; 6 x USB rear; 2 x USB internal; 1 x VGA; 1 x Serial (RS-232, 9pin, 16 byte FIFO, 16550 compatible); 1 (optional) x Parallel (25pin with EPP and ECP); 1 x Ethernet (RJ-45); 1 (DVI-D) x DVI; 1 (optional) x eSATA; 2 x Mouse / Keyboard (PS/2)
Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Realtek ALC663
10/100/1000 Mbit/s Realtek RTL 8111E
175 x 425 x 353 mm
Power supply efficiency (at 230 V; 20% / 50% / 100% load): 83% / 86% / 85%
ENERGY STAR® 5.0, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply
1 year Bring-In / On-Site Service

# All-round PCs

## ESPRIMO



Fujitsu	ESPRIMO E400 E85+
	Your Flexible Economy PC
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D2990 (ATX)
Chipset	Intel® H61
Processor type, Second level cache, Processor frequency	Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i5-2320 processor, 6 MB, 3.0 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Memory	Up to 8 GB, 2 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
Controller functions	Serial ATA II (3 Gbit), NCQ, AHCI
Drives (optional)	MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch SSD SATA, 128 GB, 2.5-inch
Drive bays	1 x 3.5-inch external bay 1 x 3.5-inch internal bay 1 x 5.25-inch external bay
Slots	2 x PCI-Express x1 1 x PCI-Express 2.0 x16
Interfaces	1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; optional USB 3.0 total; 8 x USB 2.0 total; 2 x USB front; 4 x USB rear; 2 x USB internal; 1 x VGA; 1 x Ethernet (RJ-45); 1 x DVI; 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Realtek RTL 8111E
Dimensions (W x D x H)	330 x 405 x 104 mm
Power efficiency	Power supply efficiency (at 230 V; 20 % / 50 % / 100 % load): 83 % / 86 % / 85 %
Special features	ENERGY STAR® 5.0, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply
Country-specific Standard Warranty and Service Level**	1 year Bring-In / On-Site Service

Fujitsu recommends Windows® 7.



ESPRIMO P400 E85+
Your Immediately Available Office PC
Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
D2990 (ATX)
Intel® H61
Intel® Core™ i7-2600 processor, 8 MB, 3.4 GHz Intel® Core™ i5-2500 processor, 6 MB, 3.3 GHz Intel® Core™ i5-2400 processor, 6 MB, 3.1 GHz Intel® Core™ i5-2320 processor, 6 MB, 3.0 GHz Intel® Core™ i5-2310 processor, 6 MB, 2.9 GHz Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz Intel® Celeron® processor G530, 2 MB, 2.4 GHz
Up to 8 GB, 2 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
4
Serial ATA II (3 Gbit), NCQ, AHCI
MultiCard Reader 20in1, USB 3.0 front con., 3.5-inch MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD-ROM, SATA I DVD Super Multi, SATA I Blu-ray Disc™ Triple Writer, SATA I
HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA III, 7200 rpm, 320 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
1 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
2 x PCI-Express x1 1 x PCI-Express 2.0 x16
1 x Audio: line-in / microphone; 1 x Audio: line-in; 1 x Audio: line-out; 1 x Front audio: headphone; 1 x Front audio: microphone; optional USB 3.0 total; 8 x USB 2.0 total; 2 x USB front; 4 x USB rear; 2 x USB internal; 1 x VGA; 1 x Ethernet (RJ-45); 1 (DVI-D) x DVI; 2 x Mouse / Keyboard (PS/2)
Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Realtek ALC663
10/100/1000 Mbit/s Realtek RTL 8111E
175 x 425 x 353 mm
Power supply efficiency (at 230 V; 20 % / 50 % / 100 % load): 83 % / 86 % / 85 %
ENERGY STAR® 5.0, EPEAT® Gold (dedicated regions), up to 86% energy efficient power supply
1 year Bring-In / On-Site Service



# All-round PCs

## ESPRIMO



Fujitsu recommends Windows® 7.

Fujitsu	ESPRIMO P400
	Your Immediately Available Office PC
Operating system*	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Facts mainboard	D2990 (ATX)
Chipset	Intel® H61
Processor type, Second level cache, Processor frequency	Intel® Core™ i3-2120 processor, 3 MB, 3.3 GHz Intel® Pentium® processor G840, 3 MB, 2.8 GHz Intel® Pentium® processor G620, 3 MB, 2.6 GHz
Memory	Up to 8 GB, 2 DIMM (DDR3) slot(s), Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
Serial ATA	4
Controller functions	Serial ATA II (3 Gbit), NCQ, AHCI
Drives (optional)	MultiCard Reader 20in1, USB 2.0, 3.5-inch DVD Super Multi, SATA I
Hard disk drive	HDD SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
Drive bays	1 x 3.5-inch external bay 2 x 3.5-inch internal bay 2 x 5.25-inch external bay
Slots	2 x PCI-Express x1 1 x PCI-Express 2.0 x16
Interfaces	1 x Audio: line-in / microphone 1 x Audio: line-in 1 x Audio: line-out 1 x Front audio: headphone 1 x Front audio: microphone optional USB 3.0 total 8 x USB 2.0 total 2 x USB front 4 x USB rear 2 x USB internal 1 x VGA 1 x Ethernet (RJ-45) 1 (DVI-D) x DVI 2 x Mouse / Keyboard (PS/2)
Graphics	Intel® HD Graphics or HD Graphics 2000 (depending on CPU), up to 1759 MB
Audio codec	Realtek ALC663
LAN	10/100/1000 Mbit/s Realtek RTL 8111E
Dimensions (W x D x H)	175 x 425 x 353 mm
Special features	-
Country-specific Standard Warranty and Service Level**	1 year Bring-In / On-Site Service

## \* Windows® XP Downgrade

### Use of Microsoft® Windows® XP

**End of October 2010** Microsoft stopped the shipment of OEM Downgrade Media for Microsoft® Windows® XP **together** with a system.

### Use of Microsoft® Windows® XP Mode in combination with Windows® 7

Windows® 7 offers the possibility to run applications in Microsoft® Windows® XP Mode. This software can be downloaded from the Microsoft webpage free of charge:

[microsoft.com/windows/virtual-pc/download.aspx](http://microsoft.com/windows/virtual-pc/download.aspx)

Following Microsoft products offer the possibility to run the Microsoft® Windows® XP Mode:

- Windows® 7 Professional
- Windows® 7 Enterprise
- Windows® 7 Ultimate

### Pre-installation of Microsoft® Windows® XP via Fujitsu project support (Customizing Service)

Fujitsu offers a special support to ship systems with Microsoft® Windows® XP pre-installed at extra costs for customers with at least 25 ordered systems annually.

Microsoft® Windows® XP for Fujitsu client systems licensed with one of the following Fujitsu Windows OEM operating systems:

- Windows® 7 Professional
- Windows® 7 Ultimate

To get further information please visit:

[ts.fujitsu.com/products/made4you/](http://ts.fujitsu.com/products/made4you/)

Recovery Media for Microsoft® Windows® XP are not shipped.

## \*\* Fujitsu Services

For today's business leaders and IT executives the question is not only what needs to be done, but how to do it quickly and effectively while still optimizing overall IT spending.

This is where Fujitsu can really help. We can provide you with a complete range of infrastructure services that allow you to deliver on this promise while reducing overall costs, improving ROI and still delivering outstanding service quality for your users.

Warranty comes standard with our products; it starts from the time of sale and is valid for a defined period of time. Minimum standard warranty is 12 months. The period and service level vary depending on product type and local regulations. Our ServicePack / Contract Hardware as part of Fujitsu's Maintenance and Support Services offering is the perfect extension on top of the standard warranty with various options of duration and of response or recovery time to fit customer needs and a flexible payment concept either up-front or on a regular basis.

For more information regarding Managed Services, Integration Services, Maintenance and Support Services or Financial Services please visit [ts.fujitsu.com/services](http://ts.fujitsu.com/services)

Expertise you can count on, wherever and whenever you need it.

In a country that is not the country of purchase, the warranty can only be claimed to the extent that the service concerned is available in the respective country. Please note that availability of all services cannot be guaranteed in all countries. The warranty agreed at the time of purchase may differ from the standard warranty stated here. In addition, as the customer you may have a right to legal claims not restricted by these warranty conditions.

Published by

## **Fujitsu Technology Solutions**

Mies-van-der-Rohe-Strasse 8,  
80807 Munich, Germany

Copyright: © Fujitsu Technology Solutions 11/2011

Printed in Germany

Realization: [www.chromedia.de](http://www.chromedia.de) (CM14663)

Order-No.: 10808-2-0911-EN

Contact: [ts.fujitsu.com/contact](http://ts.fujitsu.com/contact)

The latest technical data can be found on the Fujitsu Technology Solutions websites and in the corresponding data sheets. All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. Product pictures may vary from the original product.

**[ts.fujitsu.com](http://ts.fujitsu.com)**